

EcoMats

Absorbent barrier carpet mat



Dust Control Matting - Carpet Mats

EcoMats

Tough, long-lasting carpet mat with raised rubber borders on all 4 sides acts as a containment barrier and can hold up to 6 liters of water per square meter. The raised waffle pattern works double duty to remove and trap dirt and moisture.

Rubber reinforced borders and backing provide maximum strength.

Suitable for heavy duty traffic conditions in schools, public buildings, malls etc.

Cleated backing minimizes movement on all surfaces and keeps mat elevated allowing wet hard floors to dry underneath.

Vacuum or use extraction method to clean or hose off with water and hang to dry



General

Brand	Notrax
Category	Carpet Mats
Product Number	166
Product Family	Industrial & Commercial Matting
Product Group	Dust Control Matting
Product Name	Guzzler™
Recommended use	For placement inside entrances in schools, universities, public buildings, sports facilities, shopping malls
Shipping Location	Barendrecht 2992SB, The Netherlands
Type	Indoor/Outdoor Carpet Mat
Update Trigger	20210310-1301
Usage Intensity	Heavy Traffic
Colors	Charcoal, grey, brown
Sizes/weight	60x90 cm / 2,7 kg
	90x120 cm / 5,1 kg
	90x150 cm / 5,9 kg
	90x300 cm / 13 kg
	120x180 cm / 11,3 kg
	120x300 cm / 17,3 kg

Technical specifications

Application	Loose lay carpet mats
Edges	4
Material backing	Natural rubber (68% recycled)
Material top	carpet top consisting of absorbing Decalon yarns
Process	Tufted loop pile moulded in to waffle pattern on to a rubber base
Pile weight (g)	830 gram/m ²
Total weight	4,4 kg/m ²
Thickness	10,5 mm
Custom sizes	N/A

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled material	68% of the backing(recycled natural rubber)
Rohs US	Rohs Compliant (Restriction of Hazardous Substances)
Warranty	3 years. (4-5 years durability)

Product testing

Test	Norms	Results
Abraison resistance	ASTM D3884	3,1% weight loss
Colour fastness to light	AATCC 16E	Rating 5
Accelerated wear test by sim floor machine	U.S.	14,48%
Accerated soiling	U.S.	4
Anti-slip	DIN51130 / BGR181	R11
Water retention	U.S.	Up to 6 litres/ sqm.
Sanitary epidemiologic test	GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.229.P.044984.07.09
Fire testing		
Fire rating EU	DOC-FF-1-70	Pass
Fire rating US	ASTM 2859	Pass
Surface flammability	ASTM 2859	Pass
Critical radiant flux	ASTM E-648	0,11 watts/cm ²
Classification of the reaction to fire performance	DIN EN 13501-1	Bfl-s1



